

**排烟口PYF SDc-K(近控):**常闭,手动开启,DC24V电动开启,手动复位,带反馈信号,不带温感器熔断关闭  
**PYF SDj-K(全自动):**常闭,手动开启,DC24V电动开启,DC24V电动复位,带反馈信号,不带温感器熔断关闭

1250×800-M(主型)	(900+250)×630-M	(600+250)×400-M
(1250+250)×800-M	(900+250)×600-M	(600+250)×320-M
(1250+250)×700-M	(900+250)×500-M	(500+250)×800-M
(1250+250)×630-M	(900+250)×400-M	(500+250)×700-M
(1250+250)×600-M	(900+250)×320-M	(500+250)×630-M
(1250+250)×500-M	(800+250)×800-M	(500+250)×600-M
(1250+250)×400-M	(800+250)×700-M	(500+250)×500-M
(1250+250)×320-M	(800+250)×630-M	(500+250)×400-M
(1200+250)×800-M	(800+250)×600-M	(500+250)×320-M
(1200+250)×700-M	(800+250)×500-M	(400+250)×800-M
(1200+250)×630-M	(800+250)×400-M	(400+250)×700-M
(1200+250)×600-M	(800+250)×320-M	(400+250)×630-M
(1200+250)×500-M	(700+250)×800-M	(400+250)×600-M
(1200+250)×400-M	(700+250)×700-M	(400+250)×500-M
(1200+250)×320-M	(700+250)×630-M	(400+250)×400-M
(1100+250)×800-M	(700+250)×600-M	(400+250)×320-M
(1100+250)×700-M	(700+250)×500-M	(320+250)×800-M
(1100+250)×630-M	(700+250)×400-M	(320+250)×700-M
(1100+250)×600-M	(700+250)×320-M	(320+250)×630-M
(1100+250)×500-M	(630+250)×800-M	(320+250)×600-M
(1100+250)×400-M	(630+250)×700-M	(320+250)×500-M
(1100+250)×320-M	(630+250)×630-M	(320+250)×400-M
(1000+250)×800-M	(630+250)×600-M	(320+250)×320-M
(1000+250)×700-M	(630+250)×500-M	(250+250)×800-M
(1000+250)×630-M	(630+250)×400-M	(250+250)×700-M
(1000+250)×600-M	(630+250)×320-M	(250+250)×630-M
(1000+250)×500-M	(600+250)×800-M	(250+250)×600-M
(1000+250)×400-M	(600+250)×700-M	(250+250)×500-M
(1000+250)×320-M	(600+250)×630-M	(250+250)×400-M
(900+250)×800-M	(600+250)×600-M	(250+250)×320-M
(900+250)×700-M	(600+250)×500-M	